


# MINIAIR

design: Roberto Mantovani



**Supply current**  
 Courant d'alimentation  
 Corriente de alimentación  
**500mA (V<sub>f</sub> 2.9V)**

**Power**  
 Pouissance  
 Potencia  
**1.5W**



CCT	Flux	CRI
2700K	128 lm	93
3000K	133 lm	93
4200K	154 lm	93



## Code Construction

Construction du code produit  
 Construcción del código de producto

**MXR | X | X | XX**


<b>MXR</b>	<b>X</b>	<b>Emission</b> Émission Emisión	<b>X</b>	<b>Finishing</b> Finitions Acabados	<b>XX</b>	<b>Color Temp.</b> Température couleur Temperatura de color
	<b>1</b>	Single Único		<b>G</b>	<b>27</b>	2700K
	<b>2</b>	Double Doble		<b>N</b>	<b>30</b>	3000K
				<b>K</b>	<b>42</b>	4200K
				<b>Z</b>	<b>CU</b>	Custom

## Drivers

Alimentateurs  
 Alimentadores

## Series wiring

Câblage en série  
 Cableado en serie



0-10V

**FLEXA-60-PRO-CC-10V**  
 Programmable 60W CC 0-10V Dimming  
 Dimming Range: 0.1%  
**Min. 1/Max. 18 Fixtures per Driver**

Phase

**FLEXA-12-500-CC-ELV**  
 12W 500mA Constant Current  
 Dimming Range: 10%  
**Min. 2/Max. 7 Fixtures per Driver**

**FLEXA-23-500-CC-ELV**  
 23W 500mA Constant Current  
 Dimming Range: 10%  
**Min. 7/Max. 14 Fixtures per Driver**

Lutron 2-Wire Phase


**LTEA.1**  
 Hi-Lume 2-Wire Phase  
 500mA Constant Current  
 Dimming Range: 1%  
**Min. 3/Max. 6 Fixtures per Driver**

**LTEA.2**  
 Hi-Lume 2-Wire Phase  
 500mA Constant Current  
 Dimming Range: 1%  
**Min. 6/Max. 13 Fixtures per Driver**

## Optionals - Accessoires - Accesorios


### CSXT01

**Recessing box**  
 Boîtier d'encastrement  
 Caja de empotrar



### CSXT01-RAB

**Recessing box + RAB Housing**



**Note:** cable cut to measure on request  
**Note:** câble sur mesure disponible sur demande  
**Nota:** cable a medida disponible a petición

Lutron Ecosystem

**LDE.1**  
 Hi-Lume Ecosystem  
 500mA Constant Current  
 Dimming Range: 1%  
**Min. 3/Max. 10 Fixtures per Driver**

**LDE.2**  
 Hi-Lume Ecosystem Premier  
 500mA Constant Current  
 Dimming Range: 1%  
**Min. 11/Max. 16 Fixtures per Driver**