

# 4260

4000 PRO SERIES

LUMEN™  
Truss




# 4260 PROFILE

4000 Series



Cross-section dimensions:



## THE ELEGANCE OF SIMPLICITY

A new compact profile has been added to this thin series! Profile 4260 provides accent lighting at an angle of 53° to highlight products on shelves or to cut out the underside of cabinets. Exclusively: the new high-end SiLens lens made of flexible silicone, which can be installed with a simple touch of the finger. Even better, the phantom brackets perfectly conceal the surface installation. Ideal for commercial or residential applications.

### FEATURES

- Compact aluminum profile: 30.25 mm x 13 mm (1.19 in x 0.5 in)
- Custom lengths from 2 to 192 inches (4.88 m/16 ft) in aluminum
- 53° lighting angle
- 4 lumen packages: LP0 (128 lm/1.5 W/ft), LP1 (160 lm/1.5 W/ft), LP2 (255 lm/3.0 W/ft) et LP3 (308 lm/4.5 W/ft) in 8 mm width with 5 mm tape guide
- 6 color temperatures (2400 K to 6200 K), CRI 90+
- Exclusive optics: SiLens, made of flexible silicone
- End caps with milled hole on both sides for the feed wire
- Surface installation with phantom brackets
- Optional power supply unit with DC socket or hardwire connection
- Indoor use, IP22




### LED STRIP COMPATIBILITY

Compatible with LED strips up to **8 mm** wide.

### LINEAR WEIGHT


0.25 lbs/ft, 370g/m

### RECESSED INSTALLATION IN 1/2" GROOVE






## APPLICATION AREAS












## AN INTELLIGENT DESIGN

A notch on the underside completely conceals the TR64 mounting wire, giving the luminaire an even more aesthetic look. The encaps are also pass-through and the extrusion has been designed with a recess to insert the mounting clips.



PROFILE	LENSES	MOUNTING HARDWARE	LENGTH
 <p>4260 - Profile, alu</p>	 <p>SIL - SiLens</p>	 <p>PH - Phantom bracket</p>	Custom length by sections of 2 to 192 inches (6m).
 <p>4261 - Profile, black</p>	 <p>NO - No lens</p>	 <p>NO - No mounting hardware</p>	
 <p>4262 - Profile, white</p>			




4000

COLOR TEMPERATURE	LUMEN PACKAGE*	LEAD IN/OUT	USAGE	POWER SUPPLY/CONTROL	*NOTES
<ul style="list-style-type: none"> <li><span style="display: inline-block; width: 15px; height: 10px; background-color: #f4a460; border: 1px solid black; margin-right: 5px;"></span> 24 - 2400K</li> <li><span style="display: inline-block; width: 15px; height: 10px; background-color: #f4c996; border: 1px solid black; margin-right: 5px;"></span> 27 - 2700K</li> <li><span style="display: inline-block; width: 15px; height: 10px; background-color: #f4e1d9; border: 1px solid black; margin-right: 5px;"></span> 30 - 3000K</li> <li><span style="display: inline-block; width: 15px; height: 10px; background-color: #f4f2e1; border: 1px solid black; margin-right: 5px;"></span> 35 - 3500K</li> <li><span style="display: inline-block; width: 15px; height: 10px; background-color: #f4f9e1; border: 1px solid black; margin-right: 5px;"></span> 42 - 4200K</li> <li><span style="display: inline-block; width: 15px; height: 10px; background-color: #f4f9e1; border: 1px solid black; margin-right: 5px;"></span> 62 - 6200K</li> </ul>	<p>LP0 - 128 LM / 1.5W FT / 90+CRI</p> <p>LP1 - 160 LM / 1.5W FT / 90+CRI</p> <p>LP2 - 255 LM / 3.0W FT / 90+CRI</p> <p>LP3 - 308 LM / 4.5W FT / 90+CRI</p>	<p>HW3 - Hardwire 3 FT</p> <p>HW6 - Hardwire 6 FT</p> <p>HW9 - Hardwire 9 FT</p> <p>HWX - Hardwire custom FT</p> <p>DC3 - DC plug 3 FT</p> <p>DC6 - DC plug 6 FT</p> <p>DC9 - DC plug 9 FT</p> <p>DCX - DC plug custom FT</p> <p>NO - No lead</p>	<p>I - IP22 indoor dry location</p>	<p>A - Non-dimming</p> <p>B - ELV dimming 120V AC</p> <p>C - ELV dimming 120/277 VAC**</p> <p>D - 0/10V dimming 120/277 VAC</p> <p>E - Non-dimming DC plug in</p> <p>F - DMX</p> <p>G - Lutron - HI-LUME PREMIER 0,1% Eco System 24V/96W</p> <p>I - Casambi CBU-A2D-0/10V-DALI-Bluetooth 100/277 VAC</p> <p>J - Casambi CBU-PWM4-4CH-Bluetooth 100/277 VAC</p> <p>K - Casambi CBU-TED-CV-Trail edge dim-Bluetooth 120 VAC</p> <p>NO - No driver</p>	<p>*The light output is provided in lumens per foot, for a CCT of 4200K and a clear lens. Please refer to the optics page for CCT and translucency conversion factors.</p> <p>** Only available in 96W - 24V Driver</p> <div style="border: 1px solid black; padding: 2px; display: inline-block;"> <p>TITLE <b>24</b> DIMENSIONS</p> </div>



# NOTES





DESIGNED IN COLLABORATION WITH

## Glenn Boccini

*Lighting Guru*

Lighting is more of a vocation than it is a profession. After 25 years of watching the industry stand on it's head, I feel it is an exciting time to stay the course for the next 25.

We have opened Dark Tools an architectural lighting Distributor in Downtown Toronto. It is a combination lighting distributor and architectural showroom open to the trade and their clients.



## CONTACT US

### ADDRESS

9221 Edison  
Montreal, Quebec,  
H1J 1T4, Canada

### FAX

1.514.903.0649

### EMAIL

[info@lumentruss.com](mailto:info@lumentruss.com)

### PHONE

1.855.384.3384

### WEBSITE

[www.lumentruss.com](http://www.lumentruss.com)



MADE IN  
NORTH AMERICA

LUMEN™  
Truss